

LEGACY

SPORT



PRO

LEGACY®



PRO

Optional Front Blade and Sand Rake shown

LEGACY PRO

Broyhill's new Legacy PRO® multi-purpose bunker vehicle replaces their Highlander series and features 3x3 hydrostatic AWD with zero-turn radius, 18 HP air cooled engine, automatic throttle control with speeds up to 12-mph, an ergonomic operator's seat with engine kill switch, improved operator controls, 12 volt power source. The cup holder and headlight are standard features. The 40" optional front blade is equipped with both hand and foot lever controls. Depth control for center attachments is lockable and adjustable.

Cleaner air is inducted at the front of the Legacy for longer engine life. Steel hydraulic oil cooler in front of the engine provides cooler fluid temperature. The Legacy is available with standard turf or optional knobby tires. The front cover quickly removes while seat and rear housing tilt back for easy service and maintenance.

The versatile Legacy PRO® accepts a variety of attachments: front blade and 5 mid-mounts (2-scarifiers, 1-cultivator or 1-scraper blade, 1-Versa-Tine). Mid- and rear-mount attachments are controlled by standard hydraulic lift. Broyhill's sand rake offers an optional Finishing Brush that mounts on the sand rake for absolute smooth finish in your bunker. With optional hydraulic remote ports, the Legacy PRO® can tow Broyhill's TerraRoller roller-spiker, AccuAire core aerator and sprayers.



*Automatic throttle control with speeds up to 12-mph
(on both Legacy Pro and Legacy Sport)*



*Zero-turn radius and 3x3 hydrostatic AWD
(on both Legacy Pro and Legacy Sport)*

LEGACY SPORT

Multi-functional Legacy SPORT® field maintenance vehicle offers speed, comfort and AWD performance.

Broyhill introduces the all-new Legacy SPORT® turf maintenance vehicle to replace their Highlander series. It is designed to perform multi-functional tasks for turf and athletic field maintenance. Legacy Sport's all-wheel drive, 18-hp air-cooled engine, and zero-turning radius provide ultimate maneuverability and speeds up to 12-mph.

Standard features include a low-profile fiberglass body, ergonomic seat with engine kill switch, headlight, 12 volt power source, cup holder, improved operator controls, and exclusive wrap-around rear-hinged cargo box for operator accessibility while seated. Mid- and rear-hydraulic lifts accommodate a variety of attachments.

Cleaner air is inducted at the front of the Legacy for longer engine life. Steel hydraulic oil cooler in front of the engine provides cooler fluid temperature. The Legacy is available with standard turf or optional knobby tires. The front cover quickly removes while seat and rear housing tilt back for easy service and maintenance.



*18 HP air cooled engine
(on both Legacy Pro and Legacy Sport)*



Front cover easily removes while seat and rear housing tilt back for easy service and maintenance

Optional Front Blade and Infield Finisher shown



SPORT

Legacy Pro and Legacy Sport Accessories



Sand Rake - Rear mounted. 72" wide. 3-section conditioning trowel plates. 5 finishing blades, and scarifying prongs.
Item-2723



Finishing Brush - Rear mounted. 80" wide. For smooth bunker finish. Attaches to Sand Rake and Infield Finisher.
Item-2715



Versa-Tine - Mid mounted. 59.5" wide. Cultivator/scarifier/dethatcher. Hardened spring tines.
Item-2691



Sand Cultivator - Mid mounted. 74.5" wide. 8 blades. Flexible two section. Loosens sand and removes weeds.
Item-2720



Infield Finisher - Rear mounted. 74" wide. Provides a professional playing surface. 45 degree back slope level bar and diamond groove heavy rubber flails.
Item-2731



Center Grader - Mid mounted. 49" wide. 3 1/2 box scraper.
Item-2721



Fan Rake - Rear mounted. 87" wide. 5 rakes. Prepares bunkers. Attaches to sand rake.
Item-2724



Finger Scarifier - Mid mounted. 57.5" wide. Breaks up hard playing surfaces with AR400 hardened steel fingers.
Item-2692



Chisel Blade Athletic Field Scarifier - Mid mounted. 64" wide. 1" chisels.
Item-2719



Sand Rake w/ Finishing Brush - Rear mounted. Smooth bunker finish.
Item-2723 & 2715

Front Blade
40" blade equipped with hand and foot lever controls with quick attach.
Item-2722



12 Volt power Source and Cup Holder
Standard on Sport and Pro



All accessories will attach to both the Legacy Pro and Legacy Sport models

Dimensions	Length 74" Width 52" Height 29.5" @ seat, 46" @ steering wheel Weight 780 lbs. w/fluids Ground clearance 6.75" Wheel base 43.5"	Seat	One piece molded with 1/4 back support; safety seat switch with parking brake override
Tires/Wheels	Three 22 x 11-8 pneumatic tubeless turf-tread tires (optional 21 x 11-8 knobby tread ties) interchangeable demountable wheels	Body	Fiberglass; rear hood lifts for access to mechanical & hydraulic systems; removable front console for access to electrical system and steering components
Drive	Direct hydrostatic drive; 3 hydraulic motors for 3 wheel drive; 3 gal. hydraulic reservoir with oil cooler	Engine	18HP Vanguard V-twin cylinder, 4 cycle OHV, gas, air cooled with remote isolated air intake rear engine placement
Drive Controls	Foot pedal for speed control and automatic throttle control; hand throttle override	Ground Speed	Infinitely variable, 0-12 mph
Attachment Controls	Hydraulic lift/lower control for mid and rear mount attachments; reverse lockout with attachments lowered; manual center depth control	Steering	Front wheel steering; 13.5" steering wheel; 6.5:1
Brakes	Dynamic braking through hydrostatic transmission; friction type park brake	Electrical System	12 volt battery, 15 amp; 12 volt electric start with neutral safety switch
		Fuel Capacity	4 gallons unleaded gasoline
		Main Frame	Tricycle vehicle with welded tubular steel frame construction; powder coat finish
		Utility Box (Sport Version)	Fiberglass, 4 cubic feet, wrap-a-round

The Broyhill Company - Dakota City Nebraska 68731

One North Market Square, Box 475
Phone: 402.987.3412 Fax: 402.987.3601
Sales Order Placement: 800.228.1003 ext. 34
www.broyhill.com email: sales@broyhill.com
© Copyright 5/08

Distributed by:



Broyhill

when only perfection will do