



## A LOT LESS SHAKIN' GOIN' ON!

### 75% LESS VIBRATION

- Advanced Technology Vibration Isolation
- Vibration Dampening Handle Support
- 9" x 3-1/2" pneumatic rear caster wheel with lockout absorbs vibration and makes it easy to cut turf on curved landscapes




The First Name in Turf Renovation™




# JR. SOD CUTTER

# 75% LESS VIBRATION!



## NEW ADVANCED TECHNOLOGY VIBRATION ISOLATION

Four elastomeric handle isolators absorb and isolate vibration transmitted through the transmission case.



## VIBRATION DAMPENING HANDLE SUPPORT

Handle support spring supports the weight of the handle assembly while isolating vibration from the transmission case.



## CUT CURVED LANDSCAPES MORE EASILY

A new 9" x 3-1/2" pneumatic rear caster wheel absorbs vibration and makes it easy to cut turf on curved landscapes. The wheel can be locked in place for straight-line and hillside cutting.



## JR. SOD CUTTER



The Ryan® Jr. Sod Cutter has been the gold standard in the rental and commercial industry for over 50 years and remains the heavy-duty unit of choice today. The new Ryan Jr. sports a host of new features, including reduced vibration to the operator a marked 75%! A new pneumatic rear castor with lockout allows curved landscape cutting with unmatched precision. A true workhorse, the Jr. Sod Cutter packs the speed, convenience and reliability you've come to expect from Ryan®.



P.O. Box 469, Johnson Creek, WI, USA 53038-0469  
©2009 Schiller Grounds Care, Inc. All rights reserved.

**SCHILLER**  
GROUNDS CARE



A patent-pending new design and features.

A new cutting depth indicator is more accessible to the operator, indicating cutting depths up to 1-1/2".



Enhance the versatility of your Jr. Sod Cutter with optional attachments like the V-Trencher (left) and the Mole Blade kit (right). For other attachments, consult your Ryan® dealer.

## 2010 FEATURES:

- Knife cutting action now travels up to 2 inches fore and aft 20 times per second for smooth, consistent cutting depth with less vibration.
- 90% of weight rests on the cast iron drive wheel with vulcanized knobby tread for superior traction and stability during operation.
- A new adjustable belt guide ensures positive belt disengagement for longer belt life and less noise upon engagement.
- Fully assembled in crate eliminates 90 minutes of setup and adjustment for the dealer.

## SPECIFICATIONS

### 5.5-HP HONDA®

Engine Model . . . . . 4-cycle Honda® GX160; recoil start; on/off switch; low-oil alert  
Displacement . . . . . 9.9 cu. in. (163 cc)

### 6.5-HP BRIGGS & STRATTON®

Engine Model . . . . . 4-cycle Vanguard™; recoil start; dual air cleaner; low-tone muffler  
Displacement . . . . . 11.1 cu. in. (182 cc)

### UNIT

Speed . . . . . Up to 135 ft. per minute (41 m/min.)  
Cutting Width . . . . . 12 in. (305 mm) or 18 in. (457 mm)  
Cutting Thickness . . . . . Adjustable up to 2.5 in. (64 mm)

Specifications subject to change without notice. See our full line brochure for complete specifications and options.